

Auto/ L-Type Sealing Machine-AE Series

Product Image:



QR Code:



Features :

1. This machine is designed with automatic conveyor. Put the package on packing area, and sealer frame will go down to automatically seal and pack.
2. Sealer frame of machine is used by anti-sticks aluminum alloy seal knife which will not coking, smoking and make the environment be clear.
3. Available to change the time and temperature of sealer frame which are decided by the thickness of film.
4. Sealer frame is used by automatic press down. When machine is operating, package put on position, then push the "Auto button switch" and the sealer frame will go down by automatically then finish the pack.
5. Available to adjust the height of sealer which is decided by dimension of package. To add two sensors device which could selected horizontal and vertical for package.
6. This machine is including automatically scraps recycling device which is controlled by independent motor. It won't be too slack or too tie and make the film tear up. The scraps recycling device is easy to take of the wasting film.
7. Saving Electricity and resources. Just need one person to operate. Put the package on packing area, and sealer frame will go down by automatically seal and pack. It's also saving more time from working.
8. Easy operating and maintenance.

Use :

1. Sealing machine could be used in many kinds of products such as Foods, Stationery, Electronics, Hardware tools, Daily Necessities...etc., which require shrinking and packing.
2. Available film: LLDPE, PVC, OPP, PP and POF.

Specifications: (Unit: m/m)

Model	Dimension of Sealer Frame (LxW)	Mechanical Dimension (LxWxH)	Power	Electric Heating (kw)	Height of Product	Capacity	Air Pressure Exhaustion
LH-500A	500x500	1700x850x1450	220V 1Φ	1.5	120	10-15 pcs/min	4-6 kg/cm ²
LH-800A	800x600	2700x1300x1580	220V 1Φ	1.7	120	8-15 pcs/min	320.64 /min
LH-1200A	1200x600	2900x1150x1450	220V 1Φ	3.5	120	8-12 pcs/min	
LH-1500A	1500x600	3100x1150x1450	220V 1Φ	3.5	120	8-12 pcs/min	

•We can also accept your order if your requirement is beyond our standard specification.