

STRETCH WRAPPING MACHINE

WSV-1521 · WSV-1821



<< Character >>

1. The stretch film carriage is equipped with hinged drive, for smooth vertical movement. Speed is adjustable.
2. Turntable of stretch wrapping machine is equipped with hinged drive, for stable turning during pallet loading. Speed is adjustable.
3. The stretch wrapping machine controlled is by PLC system. The mechanical structure adopts the mould group to design.
4. Motor speed is controlled by inverter. It makes the machine running steadily and smoothly.
5. Two-dent design at the bottom of the turntable and it makes the forklift easily move the machine.
6. While carrying, the pole can be laid directly without dismantling. Save time and prevent the mistakes that may happen while installation.

伍晟機械股份有限公司 WUU SHENG MACHINERY. CO.,LTD

台灣台中市大里區仁化工二路117號 TEL: 886-4-24913418 FAX: 886-4-24913419
No. 117, Renhuagong 2nd Rd., (Renhua Industrial Park) Dali Dist., Taichung City 41278, Taiwan
Web-site: www.wuusheng.com.tw E-mail: wuusheng@ms16.hinet.net



STRETCH WRAPPING MACHINE

WSV-1521 · WSV-1821



7. The photoelectric cell of stretch wrapping machine can read the pallet height automatically. It is easy operating.
8. Electromagnetic brake device can adjust the tension of stretch film unlimited.
9. Pre-stretch System is optional. The purpose is to save the film material.
10. The turntable starts and stops rotation gently, and it guarantees products' safety.
11. The operator can choose manual or auto operation mode.
12. The bottom of stretch film rack has safety limit switch.

伍晟機械股份有限公司 WUU SHENG MACHINERY. CO.,LTD

台灣台中市大里區仁化工二路117號 TEL: 886-4-24913418 FAX: 886-4-24913419
No. 117, Renhuagong 2nd Rd., (Renhua Industrial Park) Dali Dist., Taichung City 41278, Taiwan
Web-site: www.wuusheng.com.tw E-mail: wuusheng@ms16.hinet.net



STRETCH WRAPPING MACHINE

WSV-1521 · WSV-1821



<< Specification >>

Items	WSV-1521	WSV-1821
Model	Stretch wrapping machine	Stretch wrapping machine
Power	3 phase 220v/380v/415v/440v	3 phase 220v/380v/415v/440v
Power Consumption	1.2KW	1.2KW
Wrapping Height	2100 mm	2100 mm
Turntable Diameter	1500mm	1800mm
Turntable Speed	5~15 RPM (speed adjustable)	5~15 RPM (speed adjustable)
Stretch Film Specification	PE stretch film Internal diameter: 76mm External diameter : 350mm Width: 500mm	PE stretch film Internal diameter: 76mm External diameter : 350mm Width: 500mm
Stretch Film Thickness	17~35 Microns	17~35 Microns
Machine Size	2623 L x 1500 W x 2410Hmm	2623 L x 1800 W x 2410Hmm

伍晟機械股份有限公司 WUU SHENG MACHINERY. CO.,LTD

台灣台中市大里區仁化工二路117號 TEL: 886-4-24913418 FAX: 886-4-24913419
No. 117, Renhuagong 2nd Rd., (Renhua Industrial Park) Dali Dist., Taichung City 41278, Taiwan
Web-site: www.wuusheng.com.tw E-mail: wuusheng@ms16.hinet.net

